



MSDS AR-G

Revision Date: March 29, 2009

# Material Safety Data Sheet

## Gaseous Argon

[Section 1 : PRODUCT AND COMPANY IDENTIFICATION](#)

[Section 2 : COMPOSITION/ INGREDIENT INFORMATION](#)

[Section 3 : HAZARD IDENTIFICATION](#)

[Section 4 : FIRST AID MEASURES](#)

[Section 5 : FIRE FIGHTING MEASURES](#)

[Section 6 : ACCIDENTAL RELEASE MEASURES](#)

[Section 7 : HANDLING AND STORAGE](#)

[Section 8 : EXPOSURE CONTROLS / PERSONAL PROTECTION](#)

[Section 9 : PHYSICAL AND CHEMICAL PROPERTIES](#)

[Section 10 : STABILITY AND REACTIVITY](#)


[Section 11 : TOXICOLOGICAL INFORMATION](#)

[Section 13 : DISPOSAL CONSIDERATIONS](#)

[Section 14 : TRANSPORT INFORMATION](#)

[Section 15 : REGULATORY INFORMATION](#)

[Section 16 : OTHER INFORMATION](#)



### Section 1 : PRODUCT AND COMPANY IDENTIFICATION

**Product name:** Argon (Gaseous),

**Supplier/ Manufacturer:** Spar Chem

159, Ashoka Shopping center,  
L.T.Road, Mumbai 400 001  
INDIA TEL +91 22 2264264 FAX  
+91 22 22642640

**Emergency phone:** + 91 9867502723

### Section 2 : COMPOSITION/ INGREDIENT INFORMATION

C.A.S.	CONCENTRATION %	Ingredient Name	OSHA PEL	ACGIH TLV	OSHA STEL
7727-37-9	> 99	ARGON	NONE	SIMPLE ASPHYXIANT	NONE

### Section 3 : HAZARD IDENTIFICATION

**Emergency Overview:** Argon gas is colorless, odorless and non-flammable.

It is non-toxic. The primary health hazard is asphyxiation by displacement of oxygen.

**Route of entry:** Inhalation, skin and eye contact.

#### Effects of acute exposure

**Eye contact:** Vapor may cause a stinging sensation.

**Skin contact:** No adverse effects from gas.

**Inhalation:** May cause dizziness.  
Asphyxiant.  
Can cause vomiting.  
May result in unconsciousness.  
May cause excitation, excess salivation, rapid breathing.  
May cause headaches and drowsiness.  
May cause stinging of the nose and throat.

**Ingestion:** Not a likely route of exposure.

**Effects of chronic exposure:** Damage to retinal ganglion cells and central nervous system may occur due to the presence of carbon dioxide.

**Reproductive effects:** Oxygen deficiency during pregnancy has produced developmental abnormalities in humans and experimental animals.

### Section 4 : FIRST AID MEASURES

**Skin contact:** None required.

**Eye contact:** None required.

**Inhalation:** **RESCUERS SHOULD NOT ATTEMPT TO RETRIEVE VICTIMS OF EXPOSURE TO THIS PRODUCT WITHOUT ADEQUATE PERSONAL PROTECTIVE EQUIPMENT. At a minimum, Self-Contained Breathing Apparatus should be worn.**

Remove victim(s) to fresh air, as quickly as possible. If not breathing qualified personnel should administer artificial respiration. Get medical attention.  
If breathing is difficult, administer oxygen.

**Ingestion:** No first aid should be needed.  
Not considered a potential route of exposure.

### Section 5 : FIRE FIGHTING MEASURES

**Flammability:** Not flammable.

**Conditions of flammability:** Will not burn.

**Extinguishing media:** Use appropriate extinguishing media for surrounding fire.

**Special procedures:** Self-contained breathing apparatus required.  
Firefighters should wear the usual protective gear.  
Cool fire exposed containers with water spray.  
Personnel should be evacuated, if necessary, to upwind area.  
Remove containers from fire area if without risk.

**Auto-ignition temperature:** Not applicable.

**Flash point (°C), method:** Not applicable.

**Lower flammability limit (% vol):** Not applicable.

**Upper flammability limit (% vol):** Not applicable.

#### **Explosion Data**

**Sensitivity to mechanical impact:** Avoid impact against container.

**Explosive power:** Closed containers may rupture or explode due to pressure build-up when exposed to extreme heat.  
Cylinders are equipped with temperature and pressure relief devices but may still rupture under fire conditions.

### **Section 6 : ACCIDENTAL RELEASE MEASURES**

**Leak/Spill:** Evacuate all non-essential personnel.  
Stop leak without risk.  
Wear gloves and goggles  
Use a self-contained breathing apparatus.

Ventilate area. Monitor the surrounding area for Oxygen level.  
Oxygen must be at least 19.5% before personnel may be allowed into the area without self-contained breathing apparatus.

If the area must be entered by emergency personnel, self-contained breathing apparatus, Kevlar gloves, and appropriate foot and leg protection must be worn.

### **Section 7 : HANDLING AND STORAGE**

**Handling procedures and equipment:** Protect system components against physical damage.  
Use adequate ventilation.  
Avoid inhalation.  
Never work on a pressurized system.

If there is a leak, close the upstream valve, blow down the system by venting to a safe place, then repair the leak.

**Storage requirements:** Use storage containers, piping, valves and fittings designed for storage and distribution of Gaseous Argon. Protect cylinders against physical damage. Store in cool, dry, well-ventilated, fireproof area, away from flammable materials and corrosive atmospheres. Store away from heat and ignition sources and out of direct sunlight. Do not store near elevators, corridors or loading docks. Do not allow area where cylinders are stored to exceed 52°C (125°F).

Move cylinders with a suitable hand-truck. Do not drag, slide or roll cylinders. Do not drop cylinders or permit them to strike each other. Secure cylinders firmly. Leave the valve protection cap in-place (where provided) until cylinder is placed into service and after it is taken out of service.

Use designated CGA fittings and other support equipment. Do not use adapters. Do not heat cylinder by any means to increase the discharge rate of the product from the cylinder. Use check valve or trap in discharge line to prevent hazardous backflow into the cylinder. Do not use oils or grease on gas-handling fittings or equipment.

After use, close main cylinder valve. Replace valve protection cap (where provided). Mark empty cylinders "EMPTY".

## Section 8 : EXPOSURE CONTROLS / PERSONAL PROTECTION

### Precautionary Measures

**Gloves/Type:**



Work gloves

**Respiratory/Type:** NIOSH/MSHA approved respirator.

**Eye/Type:** As per local regulations.

**Footwear/Type:** Safety boots per local regulations.

**Clothing/Type:** Wear adequate protective clothes.

**Other/Type:** Eye wash facility should be in close proximity.  
Emergency shower should be in close proximity.

**Ventilation requirements:** Mechanical ventilation is satisfactory. Ensure oxygen concentration remains above 19.5% and Carbon Dioxide concentration does not exceed 5000 ppm, Local exhaust at points of emission preferred.

**Exposure limit of material** Simple asphyxiant.

### Section 9 : PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:** Gas

**Appearance & odor:** Colorless, odorless gas.

**Odor threshold (PPM):** Odorless.

**Vapor pressure :** Gas@ 70°F (21 °C)

**Vapor sp. gravity (air=1):** 1.38 @ 70°F (21 °C)

**Volatiles (% by volume)** 100%

**Boiling point :** -185.9°C (760 mmHg)  
-302.6°F

**Freezing point :** -189.2°C  
-308.9°F

**Solubility in water (%):** Slight.

### Section 10 : STABILITY AND REACTIVITY

**Chemical stability:** Product is stable.

**Conditions of reactivity:** Heat

**Hazardous polymerization:** Will not occur.

**Incompatible substances:** None. Argon is an inert gas

**Hazardous decomposition products:** None

### Section 11 : TOXICOLOGICAL INFORMATION

**LD50 of product, species & route:** Not available.

**LC50 of product, species & route:** Not available.

### Section 13 : DISPOSAL CONSIDERATIONS

**Waste disposal:** Gas will dissipate in air. Cylinders should be returned in the original shipping container, properly labeled, with any valve outlet plugs or caps secured and valve protection cap in place.

### Section 14 : TRANSPORT INFORMATION

**DOT/ TDG classification:**


For cylinder shipments:  
Argon, compressed  
UN 1066  
DOT Class 2.2 (Non-Flammable Gas)



[121](#) (Gas)  
**North American  
Emergency Response  
Guidebook Number:**

**Section 15 : REGULATORY INFORMATION**

**WHMIS classification:**



**DSL status:**Appears on DSL.

**Section 16 : OTHER INFORMATION**

**Definitions and other useful data:**

**CAS #:** The Chemical Abstract Service Number which uniquely identifies each constituent.

**ACGIH** - American Conference of Governmental Industrial Hygienists, a professional association which establishes exposure limits.

**TLV** - Threshold Limit Value - an airborne concentration of a substance which represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect.

**OSHA** - U.S. Occupational Safety and Health Administration.

**PEL** - Permissible Exposure Limit - The same value as a TLV, except it is enforceable by OSHA.

**IDLH** - Immediately Dangerous to Life and Health - A concentration from which one can escape within 30-minutes without suffering permanent injury.

**NATIONAL FIRE PROTECTION ASSOCIATION:**

**Health Hazard Rating Scale (Blue):**

- 0** (material that on exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials);
- 1** (material that on exposure under fire conditions could cause irritation or minor residual injury);
- 2** (materials that on intense or continued exposure under fire conditions could cause temporary incapacitation or possible residual injury);
- 3** (materials that can on short exposure could cause serious temporary or residual injury);
- 4** (materials that under very short exposure could cause death or major residual injury).

**Flammability Hazard Rating Scale (Red):**

- 0** (minimal hazard);
- 1** (materials that require substantial pre-heating before burning);
- 2** (combustible liquid or solids; liquids with a flash point of 38-93 °C [100-200 °F]);
- 3** (Class IB and IC flammable liquids with flash points below 38 °C [100 °F]);
- 4** (Class IA flammable liquids with flash points below 23 °C [73 °F] and boiling points below 38 °C

[100°F].

**Reactivity Hazard Rating Scale(Yellow):**

**0** (normally stable);

**1** (material that can become unstable at elevated temperatures or which can react slightly with water);

**2** (materials that are unstable but do not detonate or which can react violently with water);

**3** (materials that can detonate when initiated or which can react explosively with water);

**4** (materials that can detonate at normal temperatures or pressures).

**TOXICOLOGICAL INFORMATION:**

Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. Definitions of some terms:

**LD50** -Lethal Dose (solids & liquids) which kills 50% of the exposed animals;

**LC50** - Lethal Concentration (gases) which kills 50% of the exposed animals;

**ppm** concentration expressed in parts of material per million parts of air or water;

**mg/m<sup>3</sup>** concentration expressed in weight of substance per volume of air;

**mg/kg** quantity of material, by weight.

**REGULATORY INFORMATION:**

**EPA** is the U.S. Environmental Protection Agency.

**WHMIS** is the Canadian Workplace Hazardous Materials Information System.

**DOT** and **TC** are the U.S. Department of Transportation and the Transport Canada, respectively, which assign DOT and **TDG** (Transportation of Dangerous Goods) identification numbers, hazard classifications, and proper shipping name and shipping label information. This material is hazardous as defined by 49 CFR 172.101 of the US Department of Transportation and Dangerous Goods as defined by Transport Canada Transportation of Dangerous Goods Regulations.

**USE OF THIS INFORMATION:**

SPARCHEM offers this information to customers, employees, contractors, and the general public to promote the safe use of this product through awareness of product hazards and safety information. Customers and others who use or transport or sell this product to others should: 1) Disseminate this information internally to all workplace areas, employees, agents and contractors likely to encounter this product; 2) Provide supplemental hazards awareness, safety information, operation and maintenance procedures to the workplace areas and employees, agents and contractors likely to encounter this product; 3) Furnish this information to all their customers who purchase this product; and 4) Ask each purchaser or user of the product to notify its employees and customers of the product hazards and safety information.

**DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:**

SPARCHEM. has taken reasonable care in preparing this document, however, since the use of this information and the conditions of use of the product are not within the control of SPARCHEM., it is the user's obligation to determine the conditions of safe use of this product. The information in this document is offered with no warranties or representations as to accuracy or completeness and it is the responsibility of each individual to determine the suitability of the information for their particular purpose(s).



Contact Us



[www.sparchem.com](http://www.sparchem.com)